



The Ingersoll Rand 2135QXPA Series Impactool™ was built on the hardworking and respected foundation laid by the 2135TiMAX. The result is a light, quiet and powerful impact wrench that delivers an incredible level of performance and power at a cost that won't punish your wallet. The 2135QXPA is the finely tuned and finely crafted impact wrench you need to tackle the toughest jobs.

- 1 057 Nm (780 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	2135QXPA
Ordering number	47517913001
Drive size (square)	1/2 in
Torque settings (forward / reverse)	4 / 1
Other available versions:	
- kit with 10 short sockets	2135QXPA-10SK
- kit with 3 long sockets	2135QXPA-3SK

PERFORMANCE

Maximum torque in forward	700 ft-lb / 949 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Recommended fastener size	M14 in / 9/16
Free speed	11 000 rpm
Impacts per minute	1 250

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	5.8 CFM / 164 L/min
Air consumption at load	23.0 CFM / 651 L/min
Impacting sound pressure / power (ISO15744)	90.7 / 101.7 dB(A)
Free speed sound pressure / power (ISO15744)	86.0 / 97.0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	13.3 / 4.6 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.0 lb / 1.80 kg
Tool dimensions (L x W x H)	189 x 69 x 182 mm
Shipping weight	4.8 lb / 2.2 kg
Shipping dimensions (L x W x H)	216 x 242 x 84 mm
UPC / EAN code	6 63023 120102
Origin	Assembled in the USA




SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)


SK4M14

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)


Impact sockets

For the complete range, see our accessory catalogue.

04706388

2131-366

Horizontal hanger


2115-K284

45612637

Piped-away exhaust kit


33104

91486330

Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)


77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)


Filters, regulators, lubricators

For the complete range, see our accessory catalogue.


115-LBK1

04616108

Lubricant kit for Impacttools™ with composite housing


2135-THK1

80119571

Impact mechanism service kit


SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)


SK4M18

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)


4UA9

03070216

1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)


2135-BOOT

45505377

Protective tool boot


IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)


Quick Release Couplings

For the complete range, see our accessory catalogue.


10Z4

03875671

Oil, Class 1, no. 10, 0.12 L


2135-TK2

45535028

Motor service kit