



UNDERBODY SEAL (AEROSOL)

APPLICATION

- An easy to apply spray-on rubberised coating.
- Suitable for use on most vehicles and equipment.

PROPERTIES

- Protects against corrosion, prevents rust, resists salt.
- Insulates against road noise.
- Prolongs the life of treated parts.
- For use on underside of wings, sills, chassis, floor, fuel tank, bonnet and boot lid.

TYPICAL INSPECTION DATA

Colour
S.G. @ 20°C

Black aerosol liquid
Typically 0.822

DIRECTIONS FOR USE

- Remove all grease, wax, mud and ensure surface is dry. A wire brush should be used on rusted areas.
- Before spraying shake can vigorously and at intervals during use. Use in a well ventilated area.
- Hold 12 inches (30 cm) from surface and apply a light coat.
- When dry further coats can be applied to give uniform coverage.
- To remove from paintwork, wipe off at once with Hyper Clean or white spirit.

Important

Do not apply to brakes, hoses, engine, gearbox, exhaust system or moving parts.

HANDLING

- **Caution pressurized container: protect from sunlight and other heat sources.**
- Refer to Material Safety Data Sheet.

SHELF LIFE

- Five years from date of manufacture.
- Date of manufacture can be identified on the underside of the tin. The first two figures indicate the week number, the second two figures the year.