

0RS394P-1.6

te of (compilation: 06/05/2022	Revised: 03/03/2023 Version: 2 (Replaced 1)				
SECT	TON 1: IDENTIFICATION C	OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING				
l. 1	Product identifier:	0RS394P-1.6				
	Other means of identificati	ion:				
	UFI:	5EG6-A0MF-200V-PX6U				
L.2	Relevant identified uses of	f the substance or mixture and uses advised against:				
	Relevant uses: Anticorrosion p	primer. For professional users only.				
	Uses advised against: All uses	not specified in this section or in section 7.3				
1.3	Details of the supplier of the	he safety data sheet:				
1.4	Inter Cars S.A. ul. Powsińska 64 02-903 Warszawa - Polska kontakt@intercars.com www.intercars.com Emergency telephone num	ıber:				
SECT	ION 2: HAZARDS IDENTIF	ICATION				
2.1	Classification of the substance or mixture:					
	CLP Regulation (EC) No 12	272/2008:				
	Classification of this product h	has been carried out in accordance with CLP Regulation (EC) No 1272/2008.				
	Acute Tox. 4: Acute inhalation Asp. Tox. 1: Aspiration hazard					
	Carc. 2: Carcinogenicity, Cate					
	Eye Irrit. 2: Eye irritation, Cate Flam. Lig. 3: Flammable liquid					
	Repr. 2: Reproductive toxicity,	Category 2, H361				
	Skin Irrit. 2: Skin irritation, Ca Skin Sens. 1: Sensitisation, ski					
		gan toxicity — Repeated exposure, Hazard Category 2 (Oral), H373				
		toxicity, single exposure, Category 3, H335				
2.2	Label elements:					
	CLP Regulation (EC) No 12	.72/2008:				
	Danger					
	Hazard statements:					

- H319 Causes serious eye irritation. H332 Harmful if inhaled.

- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure (Oral).

Precautionary statements:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100); Xylene; 4-methylpentan-2-one; Ethylbenzene **UFI:** 5EG6-A0MF-200V-PX6U

Additional labeling:

V.O.C.: 2004/42/WE IIB(c) (540) 540

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration			
CAS: EC:	25068-38-6 500-033-5						
Index:	603-074-00-8 Non-applicable	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	15 - <25 %			
CAS:	1330-20-7	Xylene ⁽¹⁾	Self-classified				
	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	15 - <25 %			
CAS:	108-10-1 203-550-1	4-methylpentan-2-or	ATP ATP17				
REACH:	203-550-1 606-004-00-4 01-2119473980-30- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	<10 %			
CAS:	123-42-2 204-626-7 603-016-00-1 01-2119473975-21- XXXX	4-hydroxy-4-methyl	Dentan-2-one ⁽¹⁾ Self-classified				
EC: Index: REACH:		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361; STOT SE 3: H335 - Warning	2,5 - <10 %			
CAS:	100-41-4 202-849-4	Ethylbenzene ⁽¹⁾	ATP ATP06				
	601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	<5 %			
	872-50-4 212-828-1 606-021-00-7 01-2119472430-46- XXXX						
Index: REACH:		Regulation 1272/2008	Eye Irrit. 2: H319; Repr. 1B: H360D; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	<1 %			

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:



legislation

0RS394P-1.6

Date of compilation: 06/05/2022

PROFIR

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Specific concentration limit
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	% (w/w) >=10: Eye Irrit. 2 - H319
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	% (w/w) >=10: STOT SE 3 - H335

SECTION 4: FIRST AID MEASURES

4.1 **Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.


5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:



legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Profirs

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

	-
Minimum Temp.:	5 °C
Maximum Temp.:	25 °C

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE (continued)

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
Xylene	IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³	
4-methylpentan-2-one	IOELV (8h)	20 ppm	83 mg/m ³	
CAS: 108-10-1 EC: 203-550-1	IOELV (STEL)	50 ppm	208 mg/m ³	
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³	
N-methyl-2-pyrrolidone	IOELV (8h)	10 ppm	40 mg/m ³	
CAS: 872-50-4 EC: 212-828-1	IOELV (STEL)	20 ppm	80 mg/m ³	

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ($700 < MW < 1100$)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 25068-38-6	Dermal	Non-applicable	Non-applicable	0,75 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	4,93 mg/m ³	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	11,8 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	208 mg/m ³	208 mg/m ³	83 mg/m ³	83 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
4-hydroxy-4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-42-2	Dermal	Non-applicable	Non-applicable	467 mg/kg	Non-applicable
EC: 204-626-7	Inhalation	Non-applicable	240 mg/m ³	32,6 mg/m ³	Non-applicable
N-methyl-2-pyrrolidone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 872-50-4	Dermal	Non-applicable	Non-applicable	4,8 mg/kg	Non-applicable
EC: 212-828-1	Inhalation	Non-applicable	Non-applicable	14,4 mg/m ³	40 mg/m ³

DNEL (General population):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ($700 < MW < 1100$)	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
CAS: 25068-38-6	Dermal	Non-applicable	Non-applicable	0,0893 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	0,87 mg/m ³	Non-applicable



legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Revised: 03/03/2023

		Short	exposure	Lon	g exposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicab
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicab
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicab
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicab
EC: 203-550-1	Inhalation	155,2 mg/m ³	155,2 mg/m ³	14,7 mg/m ³	14,7 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicab
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicab
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicab
4-hydroxy-4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicab
CAS: 123-42-2	Dermal	Non-applicable	Non-applicable	33 mg/kg	Non-applicab
EC: 204-626-7	Inhalation	Non-applicable	Non-applicable	5,8 mg/m ³	Non-applicab
N-methyl-2-pyrrolidone	Oral	Non-applicable	Non-applicable	0,85 mg/kg	Non-applicab
CAS: 872-50-4	Dermal	Non-applicable	Non-applicable	2,4 mg/kg	Non-applicab
EC: 212-828-1	Inhalation	Non-applicable	Non-applicable	3,6 mg/m ³	4,5 mg/m ³
PNEC:					
Identification					
reaction product: bisphenol-A-(epichlorhydrin) ($700 < MW < 1100$)	STP	10 mg/L	Fresh water		0,006 mg/L
CAS: 25068-38-6	Soil	0,065 mg/kg	Marine water	Marine water 0	
EC: 500-033-5	Intermittent	0,018 mg/L	Sediment (Fresh	water)	0,341 mg/kg
	Oral	0,011 g/kg	Sediment (Marin	e water)	0,034 mg/kg
Xylene	STP	6,58 mg/L	Fresh water		0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water		0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh	water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marin	e water)	12,46 mg/kg
4-methylpentan-2-one	STP	27,5 mg/L	Fresh water		0,6 mg/L
CAS: 108-10-1	Soil	1,3 mg/kg	Marine water		0,06 mg/L
EC: 203-550-1	Intermittent	1,5 mg/L	Sediment (Fresh	water)	8,27 mg/kg
	Oral	Non-applicable	Sediment (Marin	e water)	0,83 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water		0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water		0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh	water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marin	e water)	1,37 mg/kg
4-hydroxy-4-methylpentan-2-one	STP	100 mg/L	Fresh water		2 mg/L
CAS: 123-42-2	Soil	0,3 mg/kg	Marine water		0,2 mg/L
EC: 204-626-7	Intermittent	1 mg/L	Sediment (Fresh	water)	7,4 mg/kg
	Oral	Non-applicable	Sediment (Marin	e water)	0,74 mg/kg
N-methyl-2-pyrrolidone	STP	10 mg/L	Fresh water		0,25 mg/L
CAS: 872-50-4	Soil	0,07 mg/kg	Marine water		0,025 mg/L
EC: 212-828-1	Intermittent	5 mg/L	Sediment (Fresh	water)	1,09 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,109 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation PROFI RS

Revised: 03/03/2023

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Date of compilation: 06/05/2022

Version: 2 (Replaced 1)

0RS394P-1.6

	Pictogram	PPE	Labelling	CEN Standard		Remarks
	Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	c	place when there is a taste or smell of the ontaminant inside the face mask. If the contaminant comes with warnings it is commended to use isolation equipment.
C	Specific protection	n for the hands		1		
	Pictogram	PPE	Labelling	CEN Standard		Remarks
	Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020		ace the gloves at any sign of deterioration.
D		d has therefore to be che			terial car	n not be calculated in advance with
	Pictogram	PPE	Labelling	CEN Standard		Remarks
	Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018		daily and disinfect periodically according to nanufacturer 's instructions. Use if there is a risk of splashing.
E	Body protection				-	
	Pictogram	PPE	Labelling	CEN Standard		Remarks
	Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	Fo	r professional use only. Clean periodically ording to the manufacturer's instructions.
	Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Re	eplace boots at any sign of deterioration.
F	Additional emerge	ency measures				
	Emergency mea	asure St	andards	Emergency mea	asure	Standards
	Emergency sho	ISO 3864-1:20	SI Z358-1 11, ISO 3864-4:20	11 Eyewash stati	ons	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
In						mmended to avoid environmental
	N 9. PHYSICAL /	AND CHEMICAL PROP	FRTIFS			
				~		
		sic physical and chemi	cal properties	5.		
-	pearance: ysical state at 20 ^o	c.	Liqui	id		
	pearance:	C.	Dens			
	lour:		_	Grey		
()	iouri			0.07		
	ot relevant due to the r	nature of the product, not prov	iding information r	property of its hazards.		





0RS394P-1.6

ite of	compilation: 06/05/2022 Revised: 03/03/2023	Version: 2 (Replaced 1)
SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	ES (continued)
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	135 °C
	Vapour pressure at 20 °C:	948 Pa
	Vapour pressure at 50 °C:	4851,16 Pa (4,85 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	1450 - 1470 kg/m³
	Relative density at 20 °C:	1,45 - 1,47
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	<20,5 mm²/s
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	24 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	346 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard cla	isses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Non-applicable *
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing inf	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:



legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Profir

Revised: 03/03/2023 Version: 2 (Replaced 1)

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:


The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
 - IARC: Xylene (3); Ethylbenzene (2B); 4-methylpentan-2-one (2B); Titanium dioxide (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging fertility or the unborn child
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.



legislation

0RS394P-1.6



Date of compilation: 06/05/2022 Re

Revised: 03/03/2023 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	cute toxicity	Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
4-hydroxy-4-methylpentan-2-one	LD50 oral	3002 mg/kg	Rat
CAS: 123-42-2	LD50 dermal	Non-applicable	
EC: 204-626-7	LC50 inhalation	Non-applicable	
4-methylpentan-2-one	LD50 oral	Non-applicable	
CAS: 108-10-1	LD50 dermal	Non-applicable	
EC: 203-550-1	LC50 inhalation	11 mg/L (4 h)	Rat
N-methyl-2-pyrrolidone	LD50 oral	>5000 mg/kg	Rat
CAS: 872-50-4	LD50 dermal	>5000 mg/kg	Rat
EC: 212-828-1	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Identification Concentratio		Species	Genus
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
4-methylpentan-2-one	LC50	900 mg/L (48 h)	Leuciscus idus	Fish
CAS: 108-10-1	EC50	862 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-550-1	EC50	980 mg/L (48 h)	Scenedesmus subspicatus	Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
4-hydroxy-4-methylpentan-2-one	LC50	110 mg/L (96 h)	Oryzias latipes	Fish
CAS: 123-42-2	EC50	1000 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-626-7	EC50	1000 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
N-methyl-2-pyrrolidone	LC50	832 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 872-50-4	EC50	4897 mg/L (48 h)	Daphnia magna	Crustacean
EC: 212-828-1	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100)	NOEC	Non-applicable		
CAS: 25068-38-6 EC: 500-033-5	NOEC	0,3 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
4-methylpentan-2-one	NOEC	Non-applicable		
CAS: 108-10-1 EC: 203-550-1	NOEC	78 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
4-hydroxy-4-methylpentan-2-one	NOEC	Non-applicable		
CAS: 123-42-2 EC: 204-626-7	NOEC	100 mg/L	Daphnia magna	Crustacean
N-methyl-2-pyrrolidone	NOEC	Non-applicable		
CAS: 872-50-4 EC: 212-828-1	NOEC	12,5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degra	adability	Biodegradab	ility
reaction product: bisphenol-A-(epichlorhydrin) ($700 < MW < 1100$)	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 25068-38-6	COD	Non-applicable	Period	28 days
EC: 500-033-5	BOD5/COD	Non-applicable	% Biodegradable	0 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
4-methylpentan-2-one	BOD5	2,06 g O2/g	Concentration	100 mg/L
CAS: 108-10-1	COD	2,16 g O2/g	Period	14 days
EC: 203-550-1	BOD5/COD	0,95	% Biodegradable	84 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
4-hydroxy-4-methylpentan-2-one	BOD5	Non-applicable	Concentration	57.5 mg/L
CAS: 123-42-2	COD	Non-applicable	Period	28 days
EC: 204-626-7	BOD5/COD	Non-applicable	% Biodegradable	98,51 %
N-methyl-2-pyrrolidone	BOD5	1,09 g O2/g	Concentration	100 mg/L
CAS: 872-50-4	COD	1,6 g O2/g	Period	28 days
EC: 212-828-1	BOD5/COD	0,68	% Biodegradable	73 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential BCF 4 Pow Log 2.8	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100)	BCF	4
CAS: 25068-38-6	Pow Log	2.8
EC: 500-033-5	Potential	Low

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

*** * * * * PROFIRS**

0RS394P-1.6

Date of compilation: 06/05/2022

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bic	Bioaccumulation potential		
Xylene	BCF	9		
CAS: 1330-20-7	Pow Log	2.77		
EC: 215-535-7	Potential	Low		
4-methylpentan-2-one	BCF	2		
CAS: 108-10-1	Pow Log	1.31		
EC: 203-550-1	Potential	Low		
Ethylbenzene	BCF	1		
CAS: 100-41-4	Pow Log	3.15		
EC: 202-849-4	Potential	Low		
4-hydroxy-4-methylpentan-2-one	BCF	0.5		
CAS: 123-42-2	Pow Log			
EC: 204-626-7	Potential	Low		
N-methyl-2-pyrrolidone	BCF	0.23		
CAS: 872-50-4	Pow Log	-0.46		
EC: 212-828-1	Potential	Low		

12.4 Mobility in soil:

Identification	Absorp	tion/desorption	Volat	ility
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
4-methylpentan-2-one	Кос	Non-applicable	Henry	Non-applicable
CAS: 108-10-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-550-1	Surface tension	2,35E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene	Кос	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
4-hydroxy-4-methylpentan-2-one	Кос	1	Henry	Non-applicable
CAS: 123-42-2	Conclusion	Very High	Dry soil	Non-applicable
EC: 204-626-7	Surface tension	2,963E-2 N/m (25 °C)	Moist soil	Non-applicable
N-methyl-2-pyrrolidone	Кос	Non-applicable	Henry	Non-applicable
CAS: 872-50-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 212-828-1	Surface tension	4,007E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP6 Acute Toxicity, HP7 Carcinogenic, HP10 Toxic for reproduction, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage **Waste management (disposal and evaluation):**

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

0RS394P-1.6

Date of compilation: 06/05/2022

Profirs

4

Revised: 03/03/2023

Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land: With regard to ADR 2021 and RID 2021

With regard to AI	DR 202	1 and RID 2021:	
	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
$\langle \simeq \rangle$		Labels:	3
	14.4	Packing group:	III
3	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of da	ngero	us goods by sea:	
With regard to IM	1DG 40	-20:	
	14.1	UN number or ID number:	UN1263
		UN number or ID number: UN proper shipping name:	UN1263 PAINT
	14.2		
*	14.2	UN proper shipping name:	PAINT
	14.2 14.3	UN proper shipping name: Transport hazard class(es):	PAINT 3
	14.2 14.3 14.4	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant:	PAINT 3 3
3	14.2 14.3 14.4	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant:	PAINT 3 3 III
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant:	PAINT 3 3 III
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user	PAINT 3 3 III No
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations:	PAINT 3 3 III No 223, 955, 163, 367
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9
3	14.2 14.3 14.4 14.5 14.6 14.7	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Maritime transport in bulk according to IMO instruments:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L
Transport of da	14.2 14.3 14.4 14.5 14.6 14.7	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Maritime transport in bulk according to IMO	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



0RS394P-1.6


te of compilation: 06/	05/2022	Revised: 03/03/2023	Version: 2 (Replaced 1)		
SECTION 14: TRA	NSPORT	INFORMATION (continued)			
3	14.2 14.3 14.4 14.5 14.6	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user Physico-Chemical properties: Maritime transport in bulk according to IMO instruments:	UN1263 PAINT 3 3 III No see section 9 Non-applicable		
SECTION 15: REG					
		• • •	ation specific for the substance or		_
		5	on (EC) No 1907/2006 (REACH): N-met		e
		·	n List") and sunset date: Non-applicabl	e	
		· · ·	lete the ozone layer: Non-applicable		
		(EU) No 528/2012: Non-applicable			
	(EU) No 64	19/2012, in relation to the import a	and export of hazardous chemical produ	ucts: Non-applic	able
Seveso III:					
Section		Description	n	Lower-tier requirements	Upper-tier requirements
P5c Fl	AMMABLE L	IQUIDS		5000	50000
etc): Shall not be us —ornamental and ashtrays, —tricks and jo —games for or Contains N-me concentration included in the workers of 14, used, as a sub manufacturers conditions to e paragraphs 1 a use, as a solve Specific prov It is recommen	eed in: articles inte kes, he or more thyl-2-pyr equal to or relevant of stance on and down msure that and 2, the int or react isions in heded to usin order to o	ended to produce light or colour ef e participants, or any article intend rolidone. 1. Shall not be placed or r greater than 0,3 % after 9 May 2 chemical safety reports and safety for exposure by inhalation and 4,8 its own or in mixtures in a concen istream users take the appropriate c exposure of workers is below the obligations laid down therein shall tant in the process of coating wire terms of protecting people or e the information included in this s		example in orn mental aspects. n or in mixtures nd downstream (DNELs) relating Shall not be ma after 9 May 202 de the appropria By way of derog lacing on the m	in a users have to exposure of nufactured, or 0 unless te operational gation from arket for use, or pecific risk
-		ected by sectorial legislation			
15.2 Chemical saf					
The supplier h	as not carı	ried out evaluation of chemical safe	ety.		

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific Profirs

legislation 0RS394P-1.6



PROFIRS

legislation 0RS394P-1.6

Date of compilation: 06/05/2022	Revised: 03/03/2023	Version: 2 (Replaced 1)	
SECTION 16: OTHER INFORMATION (continued)			
ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Dose 50 EC50: Effective concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer			

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.